



Cavity Wax Clear Aerosol

Cavity Wax Clear Aerosol is a high performance silicone free wax coating for cavity protection of box sections, door skins and engine compartments on automotive vehicles. The material is non drip and demonstrates excellent penetration characteristics. This enables optimum protection for hard to access areas.

Part No.	Description	Size
472125	Cavity Wax Clear Aerosol	500ml

ADDITIONAL INFORMATION

APPLICATION

Ensure all surfaces to be applied are clean, dry and rust free. Shake Aerosol can for 2 - 3 minutes.

Apply 1 - 2 light even coats.

For cavities, spray through the extended nozzle attachment.

Drying time: 5 hours

optimum corrosion protection

penetrates and isolates existing rust

withstands metal temperature of 90°C

silicone free

non drip

non clog nozzle

Base	Waxes, corrosion inhibitors
Density	0.679 kg/L DIN 51757
Viscosity	- Pleuger RVT sp.4, 12rpm
Colour	Clear (Transparent)
Flashpoint	<20°C ASTM D 1320-67
Drying time	3-4 hours
Salt spray test	1000 Hours SS DIN 53210
Cleaning	White spirit
VOC Content	289 g/aerosol
Shelf-life	18 months



INDASA

INDASA Abrasives (UK) Ltd
Viking Works, Greenstead Rd,
Colchester, CO1 2ST
Tel: 01206 870366
Fax: 01206 860525
Email: office@indasa.co.uk