



Product Sheet

DIRECT GLAZING SEALANT



DIRECT GLAZING SEALANT

One part PU adhesive for installation of bonded windscreens

Install and drive
away within 2 hours

Excellent adhesion to both metal and
glass substrates (cleaned and primed)



High shear strength



UV resistant



Ease of application



Product Sheet

DIRECT GLAZING SEALANT

Features and Benefits

TUV certificate



Quality assured

High strength sealant adhesive



Excellent bonding properties

2 hours drive away time



Increased efficiency

Substrates

Primers

Primed Surface

Metal

Hard Metal

Glass

Applications

Windscreen replacement

Automotive bodywork



Product Sheet

DIRECT GLAZING SEALANT

Suited for



Automotive Refinishing

Type



INDASA

INDASA

Technical Specifications

Elongation (ISO 37 DIN 53504)	>= 300%
Tensile Strength (ISO 37 DIN 53504)	>= 9 N/mm ²
Colour	Black
Binder	Polyurethane based compound
Curing Mechanism	Moisture curing
Shore A (23°C and 50% r.h.)	55
Tack-Free Time (23°C and 50% r.h.)	15 min
Application Temperature	5 - 40 °C
Temperature Resistance	-40 to 100 °C
Capacity	310 ml
Package Qty.	12
Shelf Life	12 months