










Intended use

Mipa Anti-Silikon-Zusatz avoids cratering and improves the flow when coating surfaces with residues of silicone, polish, wax and grease. Suitable for Mipa 2K paints (OC/AC/PUR/PUR HS) and Mipa paints based on synthetic resins.

Quantity to add: 2 up to max. 5 % Mipa Anti-Silikon-Zusatz to base paint or to base paint after addition of hardener in case of 2K paint materials.

Spreading rate: --

Processing instructions

	Colour colourless						
	Mixing ratio						
	Hardener		by weight (lacquer : hardener)		by volume (lacquer : hardener)		
	--	--	--	--	--	--	--
	Hardener						
	for complete paintwork				for partial paintwork		
	--	--	--	--	--	--	--
	Pot life						
	--	--	--	--	--	--	--
	Thinner						
	--	--	--	--	--	--	--
	Spray viscosity						
	Gravity spray gun				Airmix/Airless		
	--	--	--	--	--	--	--
	Application method						
	Application method	Hardener	Pressure (bar)	Nozzle (mm)	spray passes	Thinner	
	--	--	--	--	--	--	--
	Flash-off time						
	--	--	--	--	--	--	--
	Dry coat thickness						
	--	--	--	--	--	--	--
	Drying time						
	Object temperature	dust dry	set to touch	ready for assembly	sandable	recoatable	
	--	--	--	--	--	--	--

Note

- Storage:** at least 3 years in unopened original container
- VOC Regulation :** –
- Processing conditions:** from +10 °C and up to 80 % relative air humidity. Ensure an adequate air ventilation.
- Processing instructions:** The use of Mipa Anti-Silikon-Zusatz has no impact on drying times.